

8525 Vehicle Mount Computer

c/w Standard radio dome, Standard temp, 8.8 inch 5-wire colour touch screen
 128 MB RAM, 32 MB Flash, 10-90 Volts, standard mount kit
 (or 8x55 quick release mount kit with adapter brackets)

Temperature Range

Temp, Standard (-4F to 122F, -20C to 60C)
 Temp, Freezer Condensing with heater (-22F to 140F, -30 to 60C)

Display

Screen Blanking (turns off display when vehicle in motion)

Keyboard

Keyboard, ABC
 Keyboard, AZERTY
 Keyboard, QWERTY

**Radio Options**

Radio, 2.4 GHz 802.11b, direct sequence (DS), internal antenna
 Radio, 2.4 GHz 802.11b, direct sequence (DS), external antenna (choose antenna option)
 Dome, Low Profile, for Radio (option for internal antenna radio only) **(future availability)**

RA1001

Radio, Narrow Band

or

Radio Options

Radio, Bluetooth

Software

Software, WINCE.NET & Internet Explorer
 Software, WINCE.NET OpenTekTerm (Charge for each emulation type. Per terminal)
 Software, Naurtech CETerm Smart Client
 Software, WIN CE.NET with JAVA
 Software, IBM JVM
 Software, AirFortress™ CE.NET

Mounting Options**Mounting**

MT3100 Mount, 8525/8530 Standard Cradle, kit
 MT3200 Mount, Cradle 8255/60-style Quick disconnect and plate with adapter brackets for 8525
 MT3100+MT330 Mount, 8525/8530 RAM with 2 round bases (Standard Cradle included)
 MT3100+MT331 Mount, 8525/8530 RAM with 2 vesa bases (Standard Cradle included)
 MT3100+MT332 Mount, 8525/8530 RAM with 1 round base and 1 vesa base (Standard Cradle included)
 MT3100+MT340 Mount, 8525/8530 Quick Release 8525 with 20 degree tilt (Standard Cradle included) **(future availability)**
 MT3100+MT350 Mount, 8525/8530 Swivel with Quick Release (Standard Cradle included) **(future availability)**

8525 Accessories**Extra Mounts & Holding Devices**

MT3100 Mount, 8525/8530 Standard Cradle, kit
 MT3200 Mount, Cradle 8255/60-style Quick disconnect and plate with adapter brackets for 8525
 MT3210 Mount Adapter Bracket Kit for 8x55 quick release mount
 MT3301 Mount only RAM with 2 round bases
 MT3311 Mount only RAM with 2 vesa bases
 MT3321 Mount only RAM with 1 round base and 1 vesa base
 MT3401 Mount only 8525 Quick Release (with 20 degree tilt) **(future availability)**
 MT3501 Mount only 8525 Swivel **(future availability)**
 Mounting structure Cantilevered horizontal
 Mounting structure full-width horizontal
 8837 Mount, one piece multi-mount
 8824 Mount heavy-duty pedestal with Locking Joint
 8826 Mount resilient Helical Coil

Power, Batteries & Chargers

8741	Power supply, Transient Suppressor
8821	Cord power extension
8870	Cart, Battery w/ cables & enclosure (32Ah@12V)
8871	Charger single unit for 18648 cart battery
PS1400	Power Supply 18V 3.3A 110/220VAC with cable

Antenna

Antenna, 2.4 GHz dipole 2 dBi reverse polarity SMA connector (choose 2 for diversity)
Antenna, 2.4 GHZ 5 dBi Mag Mount RP-SMA (choose 2 for diversity)
Antenna, 2.4 GHZ 0 dBi Mag Mount RP-SMA (choose 2 for diversity)
Antenna, Narrow Band 1/4 wave, 406-512 MHz 6" NB
Mount, Mag, Narrow Band, SMA, 12' cable

Adapters & Cables

CA1020	Cable, 6', JB5 Connector to USB slave
CA1010	Cable, 6', JB5 Connector to D9 male serial
CA1015	Cable, 6', JB5 Connector to D9 male serial null
CA2200	Cable, Aux Port (26 pin) to USB Host (x 2) and USB device
	Cable, Scanner 15' LS32xx JB5 (future availability)
	Cable, Service USB/RS232/PCON

Covering Accessories

VA 6110	Cover, Protective for 8525 Touch Screen (package of 12)
---------	---