

8530 Vehicle Mount Computer

c/w Standard radio dome, Standard temp, 10.4 inch 5-wire colour touch screen
 128 MB RAM, 64 MB Flash, 10-90 Volts, Internal UPS (back-up battery)
 standard mount kit, On-screen Keyboard
 (or 8x60 quick release mount kit with adapter brackets)

Temperature Range

Temp, Standard (-4F to 122F, -20C to 60C operation, -10C/14F cold start-up)
 Temp, Freezer Condensing with heater (-22F to 140F, -30 to 60C)- **(future availability)**

Display

Screen Blanking (turns off display when vehicle in motion)

Keyboard (external)

c/w IP 66 sealed KB connector and RAM mount keyboard mount
 Keyboard, ABC
 Keyboard, AZERTY
 Keyboard, QWERTY

**Radio Options**

Radio, RA2020 802.11b, internal antenna, direct sequence (DS)
 Radio, RA2020 802.11b, external antenna (choose antenna option), direct sequence (DS),
 Radio, RA2040 802.11g, internal antenna, direct sequence (DS),
 Radio, RA2040 802.11g, external antenna (choose antenna option), direct sequence (DS),

Radio, RA 1001, Narrowband

Dome, Low Profile, for Radio (option for internal antenna radio only) **(future availability)**

or

Radio Options

Radio, RA 4010, Bluetooth

Software

Software, WINCE.NET & Internet Explorer
 Software, WINCE.NET OpenTekTerm (Emulations charge for each emulation type. Per terminal)
 Software, Naurtech CETerm Smart Client
 Software, WIN CE.NET with JAVA
 Software, AirFortress™ CE.NET

Mounting Options**Mounting**

MT3100	Mount, 8525/8530 Standard Cradle kit
MT3200	Mount, 82xx-style Quick disconnect cradle and plate with adapter brackets for 8525/8530
MT3300	Mount, 8530 Keyboard or Terminal with RAM mount (4" arm). 2 round bases
MT3330	Mount, 8530 Keyboard or Terminal with RAM mount (4" arm). 2 vesa bases
MT3331	Mount, 8530 Keyboard or Terminal with RAM mount (4" arm). 1 vesa base (to KB) and 1 round base
MT3220	Mount, 8260 Keyboard Quick disconnect cradle and plate with adapter brackets for 8530 keyboard
MT3100+MT330	Mount, 8525/8530 RAM (12" arm) 2 round bases (Standard Cradle included)
MT3100+MT331	Mount, 8525/8530 RAM (12" arm) with 2 vesa bases (Standard Cradle included)
MT3100+MT332	Mount, 8525/8530 RAM (12" arm) with 1 round base and 1 vesa base (Standard Cradle included)
MT3100+MT340	Mount, 8525/8530 Quick Release with 20 degree tilt (Standard Cradle included) (future availability)
MT3100+MT350	Mount, 8525/8530 Swivel with Quick Release (Standard Cradle included) (future availability)
MT3402	Mount, 8530 Keyboard Quick Release with 20 degree tilt (future availability)
MT3403	Mount, 8530 Keyboard Quick Release 82XX Style
MT3600	Mount, 8530 Keyboard L Bracket to attach to any standard mount kit (RAM, Quick Release, Swivel) (make sure configurator will remove KB ram mounts if this is chosen as KB will mount directly to the L Bracket)

8530 Accessories**Extra Mounts & Holding Devices**

MT3100	Mount, 8525/8530 Standard Cradle kit
--------	--------------------------------------

MT3200	Mount, 82xx-style Quick disconnect cradle and plate with adapter brackets for 8525/8530
MT3300	Mount, 8530 Keyboard or Terminal with RAM mount (4" arm). 2 round bases
MT3330	Mount, 8530 Keyboard or Terminal with RAM mount (4" arm). 2 vesa bases
MT3331	Mount, 8530 Keyboard or Terminal with RAM mount (4" arm). 1 vesa base (to KB) and 1 round base
MT3220	Mount, 8260 Keyboard Quick disconnect cradle and plate with adapter brackets for 8530 keyboard
MT3210	Mount, Adapter Bracket Kit for 82xx quick release
MT3215	Mount, 8530 Keyboard Quick Release 82XX Style - NO PLATE
MT3301	Mount, only RAM (12" arm) with 2 round bases
MT3311	Mount, only RAM (12" arm) with 2 vesa bases
MT3321	Mount, only RAM (12" arm) with 1 round base and 1 vesa base

Mount, Cantilevered horizontal mounting structure

Mount, Full-width horizontal mounting structure

8837 Mount, One piece multi-mount

8824 Mount, Heavy-duty Pedestal with Locking Joint

8826 Mount, Resilient Helical Coil

Power, Batteries & Chargers

8741 Power supply, Transient Suppressor

8821 Cord power extension

8870 Battery, Cart w/ cables & enclosure (32Ah@12V)

8871 Charger single unit for 18648 cart battery

PS1400 Power Supply 18V 3.3A 110/220VAC with cable

Antenna

Antenna, 2.4 GHZ dipole 2 dBi reverse polarity SMA connector (choose 2 for diversity)

Antenna, 2.4 GHZ 5 dBi Mag Mount RP-SMA (choose 2 for diversity)

Antenna, 2.4 GHZ 0 dBi Mag Mount RP-SMA (choose 2 for diversity)

Antenna, Narrow Band 1/4 wave, 406-512 MHz 6" NB

Mount, Mag, Narrow Band, SMA, 12' cable

Adapters & Cables

CA1020 Cable, 6', JB5 Connector to USB slave

CA1010 Cable, 6', JB5 Connector to D9 male serial

CA1015 Cable, 6', JB5 Connector to D9 male serial null

CA2200 Cable, Aux Port (26 pin) to USB Host (x 2) and USB device

Cable, Scanner 15' LS32xx JB5

Cable, Service USB/RS232/PCON

CA2300 **Cable, 8530 Keyboard (6')**

Covering Accessories

VA6120 Cover, 8530 Touch Screen Protective (package of 12)